



Mobile Containeramp Specifications (Mobile Yard Ramp)

Steel Ramps with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
16,000	36'	70"	62"	6,100	37" – 65"	SS16-70-36PL8
16,000	36'	84"	76"	6,900	37" – 65"	SS16-84-36PL8
20,000	36'	70"	62"	6,200	37" – 65"	SS20-70-36PL8
20,000	36'	84"	76"	7,000	37" – 65"	SS20-84-36PL8
25,000	36'	70"	62"	6,300	37" – 65"	SS25-70-36PL8
25,000	36'	84"	76"	7,100	37" – 65"	SS25-84-36PL8
30,000	36'	84"	76"	7,900	37" – 65"	SS30-84-36PL8

****STOCK ITEMS****

Aluminum Ramps with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
16,000	36'	70"	62"	4,700	37" – 65"	AS16-70-36PL8
16,000	36'	84"	76"	5,600	37" – 65"	AS16-84-36PL8
20,000	36'	70"	62"	4,800	37" – 65"	AS20-70-36PL8
20,000	36'	84"	76"	5,700	37" – 65"	AS20-84-36PL8
25,000	36'	70"	62"	4,900	37" – 65"	AS25-70-36PL8
25,000	36'	84"	76"	5,920	37" – 65"	AS25-84-36PL8

Standard Features:

- Steel or Aluminum I-Beam Construction
- 6" Steel Curbs / 7" Aluminum Curbs
- 36' in Length
- 8' Level-Off
- 30" Approach Ramp
- 15" Lip
- 2 ¼" Serrated Steel Grating
- 23" Pneumatic Tires
- Double Acting Hydraulic Pump
- Positioning Sleeve
- Safety Chains

Options:

- Tow-Bar
- Solid Filled Tires